

Solis-3P(5-20)K-4G-AU

Solis Three Phase Inverters



360 degree

Features:

- Max. efficiency 98.7%
- Complies with Western Power, SA, VIC, QLD, and NSW grid requirements
- Integrate with adjustable Volt-Watt and Volt-Var function
- DRM integrated, fully comply with AS4777.2:2015
- Built-in DC-PV2 Switch (optional), comply with AS/NZS 5033 requirements
- Support 24h consumption monitoring with a smart meter
- 2 MPPT design with precise MPPT algorithm
- THDi<1.5%, low harmonic distortion against grid
- Integrated Export Power Manager(EPM)
- Multiple protections functions
- Voltage active power and reactive power



Model:

Solis-3P5K-4G-AU	Solis-3P5K-4G-AU-MX
Solis-3P6K-4G-AU	Solis-3P8K-4G-AU
Solis-3P8K-4G-AU-MX	Solis-3P9K-4G-AU
Solis-3P10K-4G-AU	Solis-3P12K-4G
Solis-3P15K-4G	Solis-3P17K-4G
Solis-3P20K-4G	

Datasheet

Model Name	Solis-3P5K-4G-AU	Solis-3P5K-4GAU-MX	Solis-3P6K-4G-AU	Solis-3P8K-4G-AU	Solis-3P8K-4GAU-MX	Solis-3P9K-4G-AU	Solis-3P10K4G-AU	Solis-3P12K-4G	Solis-3P15K-4G	Solis-3P17K-4G	Solis-3P20K-4G
Input DC											
Recommended max. PV power	10 kW	10 kW	12 kW	12 kW	12 kW	13.5 kW	15 kW	18 kW	22.5 kW	24 kW	24 kW
Max. input voltage						1000 V					
Rated voltage						600 V					
Start-up voltage						180 V					
MPPT voltage range						160-850 V					
Max. input current		22 A / 11 A					22 A / 22 A				
Max. short circuit current		30 A / 15 A					30 A / 30 A				
MPPT number/Max. input strings number		2/2					2/4				
Output AC											
Rated output power	5 kW	4.999 kW	6 kW	8 kW	7.999 kW	9 kW	10 kW	12 kW	15 kW	17 kW	20 kW
Max. apparent output power	5.5 kVA	4.999 kVA	6.6 kVA	8.8 kVA	7.999 kVA	9.9 kVA	11 kVA	13.2 kVA	16.5 kVA	18.7 kVA	22 kVA
Max. output power	5.5 kW	4.999 kW	6.6 kW	8.8 kW	7.999 kW	9.9 kW	11 kW	13.2 kW	16.5 kW	18.7 kW	22 kW
Rated grid voltage						3/N/PE, 230 V / 400 V					
Rated grid frequency						50 Hz					
Rated grid output current	7.2 A	7.2 A	8.7 A	11.5 A	11.5 A	13 A	14.4 A	17.3 A	21.7 A	24.6 A	28.9 A
Max. output current	7.9 A	7.9 A	9.5 A	12.7 A	12.7 A	14.3 A	15.9 A	19.1 A	23.8 A	27 A	31.8 A
Power Factor						>0.99 (0.8 leading - 0.8 lagging)					
THDi						<1.5%					
Efficiency											
Max. efficiency			98.3%						98.7%		
EU efficiency			97.8%						98.1%		
Protection											
DC reverse-polarity protection						Yes					
Short circuit protection						Yes					
Output over current protection						Yes					
Surge protection						Yes					
Grid monitoring						Yes					
Anti-islanding protection						Yes					
Temperature protection						Yes					
Integrated DC switch						Optional (PV2 Switch)					

General Data

Dimensions (W*H*D)	310*563*219 mm	
Weight	18.9 kg	19.8 kg
Topology	Transformerless	
Self consumption (night)	<1 W	
Operating ambient temperature range	-25 ~ +60°C	
Relative humidity	0-100%	
Ingress protection	IP65	
Cooling concept	Intelligent redundant fan-cooling	
Max. operation altitude	4000 m	
Grid connection standard	AS/NZS 4777.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530	
Safety/EMC standard	IEC 62109-1/-2, IEC 61000-6-1/-2/-3/-4	

Features

DC connection	MC4 connector
AC connection	Quick connection plug
Display	LCD
Communication	RS485, Optional: Wi-Fi, GPRS